

## Sidelong cantilever stacker



Model	Conveying media	Rail diameter (m)	Stack capacity (t/h)	Cantilever length (m)	Radius-Changing drive	Cantilever belt conveyor		Traveling mechanism speed (m/min)	Power (kw)	Weight (t)
						Belt width(mm)	Belt speed (m/s)			
DCX200/12.5	Auxiliary material	3.5	200	12.5	Hydraulic	650	2.0	18.6	35	53
DCX200/13	Auxiliary material	3.5	200	13		800	1.6	18.6	35	57
DCX300/13.5	Auxiliary material	3.5	300	13.5		800	2.0	18.6	35	58
DCX250/14.5	Auxiliary material	4.0	250	14.5		800	1.6	18.6	35	59
DCX200/15	Auxiliary material	4.0	200	15		800	1.6	18.6	40	60
DCX400/15.5	Auxiliary material	4.0	400	15.5		1000	1.6	18.3	40	63
DCX500/16	Auxiliary material	4.0	500	16		1000	2.0	18.3	45	69
DCX450/16.5	Auxiliary material	4.0	450	16.5		1000	2.0	18.3	45	70
DCX400/17	Auxiliary material	4.0	400	17		1000	1.6	18.3	45	73
DCX650/17.5	Limestone	4.0	650	17.5		1000	2.0	18.3	50	78
DCX400/19	Auxiliary material	4.0	400	19		1000	1.6	18.3	45	80
DCX850/20	Limestone	5.0	850	20		1000	2.0	20	60	86
DCX1250/22	Limestone	5.0	1250	22		1200	2.0	20	85	110
DCX1500/22.5	Limestone	5.0	1500	22.5		1200	2.0	20	90	115
DCX1800/23	Limestone	5.0	1800	23		1400	2.0	35	110	125