

[Tower Crane TCP7532](#)

1. Stationary Type

Free standing height: 64.5 m

Full jib length: 75m

Maximum load: 12ton

Tip load at 65m jib: 3.2 ton

Maximum rated radius: 75m 12t

Maximum rated radius: 70m 12t

Maximum rated radius: 65m 12t

Maximum rated radius: 60m 12t

Maximum rated radius: 55m 12t

Maximum rated radius: 50m 12t

Maximum rated radius: 45m/40m /35m/30m 12t

2. Travelling Type

Free standing height: 68.4m

Full jib length: 75m

Maximum load: 12ton

Tip load at 65m jib: 3.2 ton

Maximum rated radius: 75m 12t

Maximum rated radius: 70m 12t

Maximum rated radius: 65m 12t

Maximum rated radius: 60m 12t

Maximum rated radius: 55m 12t

Maximum rated radius: 50m 12t

Maximum rated radius: 45m/40m /35m/30m 12t

3. Internal Type

Free standing height: 93.7m

Full jib length: 75m

Maximum load: 12ton

Tip load at 65m jib: 3.2 ton

Maximum rated radius: 75m 12t

Maximum rated radius: 70m 12t

Maximum rated radius: 65m 12t

Maximum rated radius: 60m 12t

Maximum rated radius: 55m 12t

Maximum rated radius: 50m 12t

Maximum rated radius: 45m/40m /35m/30m 12t

[Tower Crane](#) [Luffing Crane](#) [Top slewing crane](#) [tower crane supplier](#) [Tower crane dealer](#) [Tower crane dealership](#) [Opencast Mining Equipment](#) [Bucket wheel Stacker](#) [chain bucket conveyors](#) [bucket wheel stacker reclaimer](#) [stacker reclaimer manufacturer](#)